



ELOTEC ASPECT

ACCESSORIES



If you have a challenging project, we can help you. Through the years, Elotec has gained unique experience in all kinds of buildings with every type of environment, and we can provide you with early and reliable detection in any installation.



● **PL 252 (PL 253) | 25 MM PLASTIC PIPE**
An internal Ra value of 1.6 contributes to avoiding build-up of dust and bacteria in the pipeline, and to ensuring optimal transportation of smoke.



● **SK 252 (SK 253) | PIPE JOINS**
Extra long sleeve couplings with applied sealant provides excellent connections in the pipeline and prevents pipes slipping apart due to temperature changes or movement.



● **BE 252 (BE 253) | BEND, 90°**
Sleeve couplings bent at 90 degrees, including the same sealant as regular couplings.



● **BE 252-45 (A/B) (BE 253-45) | BEND, 45°**
Sealant as in the standard bend. Two versions: female/female (A) and female/male (B). The "B" variant can be combined with "A" or the 90° bend to easily adapt the pipeline to twisting or difficult areas.



● **BE 255-40/100/150 | PIPEFLEX**
Flexible connection bends for pipes. Three sizes: 40, 100 and 150 cm.



● **KG 252 (KG 253) | BRANCH X/Y**
The X/Y crosspiece is used to split one pipe into two or three branches.



● **CL 250 (CL 253) | FASTENING CLIPS**
Standard fastening clips for pipelines are quickly and easily mounted in the ceiling, and the pipes are then pressed into place.



● **CL 250 W | FASTENING CLIPS**
Fastening clips for wire suspension of pipelines. Silk wire is strung through the room, and the pipeline is pressed into the clips and pushed onto the wire from one end.



● **CL 255 | FASTENING CLIPS NYLON**
Nylon clips for rooms with very variable temperatures.



● **CL 251 W | FASTENING S-HOOK FOR WIRE**
S-hooks are used for easier handling of pipes in greenhouses.



● **KM 250 | STICKER FOR SAMPLING HOLES**
Sticker for marking sampling holes. Affix so that it points towards the Aspect.



● **SNIFFER**
Sniffers are the extended arms of the pipeline, able to be stretched through ceilings from church lofts and such. This way, the pipeline may be hidden, and the system appears as virtually invisible.



● **GG 256 | PIPE BRANCH**
80 cm pipe branch for extended sampling points. Used for simple detection both over and underneath shadow curtains in greenhouses.



● **SN 253 P/S | SNIFFER, 3 M HOSE**
Sniffer with three meter hose. Cut to appropriate length during installation.



● **SN 258 M | SNIFFER, 75 CM, STEEL BRAID**
75 cm sniffer hose, protected from mice and other rodents. Mostly used in churches or office buildings.



● **PL 260 F | PLASTIC PIPE ON COIL, 120 M**
Flexible pipe made out of halogen free polyethylene. All accessories like bends, cross and joins are available.



● **EP 250 | END PLUG**
To seal the end of all pipes. Can also be used when pushing pipes through walls to avoid dirt or foreign objects in the pipeline.



● **PLP 210 007 | HUB 2-1**
The hub is designed to merge the two pipe inlets on Aspect into one.



● **THUB | THUB FOR ASPECT 2010**
Makes ELOCLEAN and VULCAN easier to install. Simple wall mounting with built-in spirit level. THUB and pipes can be mounted before attaching the ASPECT. Integrated condensation container and drain.

● *These products can be delivered in grey or red plastic, copper, aluminum, or other materials / colors.*



ELOTEC ASPECT

ACCESSORIES



AU 002 | EXHAUST KIT

Used to lead exhaust air back into rooms with large underpressure to ensure sufficient transportation of air. Can also reduce fan noise or avoid spreading odors if an ASPECT installed in a clean environment samples air from livestock rooms or similar. Extra bug-filter available (AU 000 G).



AU 003 | EXHAUST KIT

This flexible exhaust kit is used to let exhaust pipes circumvent a VULCAN or ELOCLEAN installed directly beside the Aspect.



FS 2010 | FILTER DRAWER ASPECT

Filter drawer for direct mounting in Aspect.



FI 003 KP | FILTER KIT, 5PK:

Progressive filters prevent dust from contaminating the sensors. Comes complete with frames that snap into the filter drawer for quick and easy replacement.



FI 004 KP | FILTER KIT, 5PK:

Extra fine filter, used where very small dust particles are present, e.g. garages or workshops. May need more frequent replacement than standard filters.



DIAMANT | FLOW SENSOR FILTER

Designed to protect the most sensitive components of the ASPECT against damage from extreme conditions with respect to dust and condensation, even where the ASPECT is installed in less suitable locations.



VF 250 COM | VULCAN DUST AND CONDENSATION FILTER

Install in front of ASPECT to remove both dust and condensation from the sampled air before it enters the detection chamber. Used when securing rooms with extreme amounts of dust.



THUB LK | CONDENSATION RESERVOIR

Ensures safe overflow of condensed water from the THUB in installations with high humidity. Mounts to the side of ASPECT.



LK 501 | CONDENSATION RESERVOIR

Ensures safe overflow of condensed water from the aspiration pipeline in installations with high humidity. UV-resistant plastic withstands direct sunlight over time. Mounts on the pipeline.



ELOCLEAN | CLEANING SYSTEM FOR PIPES

Easy and safe cleaning of pipes, no compressor needed. Intended for extremely dusty environments. Manual or automatic cleaning.



PH12-36B | POWERHOUSE

12V battery enclosure intended for use together with Aspect's internal charger. The enclosure is rated IP44. EN 54-4 compliant.



BA 1800 | BATTERY, LIFEPO4, 12,8V 18AH

Battery for Elotec ASPECT.



ASPECT-WIFI | DIAGNOSTICS MODULE

This module and its companion app, Aspect Tool, greatly simplifies commissioning, configuration and service.



IB 2010 | FOR OTHER FIRE ALARM PANELS

Module for connecting Elotec Aspect to third-party conventional or adressable panels.



SENSORKIT | G, GN, GH, L, OIL

Sensorkit for Aspect Grizzle, Lazeer, Oil. Different sensitivity levels for class A/B/C.



ELOCUT 2 | PIPE CUTTING TOOL

ELOCUT 2 makes clean cuts without deforming pipes.



ASP BIT | SPECIAL DRILL BITS

Selected bits for drilling correctly sized pipe holes as calculated by Elotec PipeDraw.



ELOVAC | MANOMETER

Easy-to-use tool for controlling sufficient suction (vacuum) in the pipelines.



SS 001 | CLEANING SYRINGE

Syringe designed for cleaning the internal flow sensor of Aspect.



TS 001 | SMOKE PEN

Smoke pen tests aspirating and point smoke detectors effectively. The cotton wick provides a steady flow of smoke.